	Subdissily CLASSIFICATION	ENI EN	INDEP	35 U.S.C. 37		PATENT NUMBER
	Class (SSUE CLAS	U.S. <b>UTILI</b>		7		
		BCANNED THE	.I.P.E.		ATENT DATE	
	APPLICATION NO. CONT/PRIOR   09/980701 D F	428	UBCLASS	ART UNIT	EXAMINER Ruddoc	i.
	Taijiro Matsui Hiroshi Imagawa Tsuneo Kayama Shinji Aso	Jero 12 - 15		<u>'</u>		······································
	Thermally insulat method for produc execution thereof	ing material tion thereof	. baving , and u	exceller se therec	rt durability of and method	r and i for PTO-2040 1299
						Tarana Tarana
	OUTOWAY -	ISSUING	(の大学・事業のいないない)	FICATIO	V FERENCE(S)	TOWNS
	GVSD GUICEAS	SI- CLASS	. Sú	BCLASS (ON	SUBCLÁSS PER B	LOCK)
	INTERNATIONAL CLASSIFICAT	ion		a diparting	ineria.	
					Continued on Issue Slip	Inside File Jacket
• 21	TERMINAL	DRAWINGS			CLAIMS ALLOWED	
	DISCLAIMER	Sheets Drwg.	Figs. Drwg.	Print Fig.	Total Claims	Print Claim for O.G
W.	The term of this patent subsequent to (date)				NOTICE OF ALL	OWANCE MAILED
	has been disclaimed.	(Assistant Examiner) (Date)			24 - 40 years	
	not extend beyond the expiration date of U.S Patent. No.	<b>'</b>			Amount Due	JE FEE Date Paid
		(Primary Examiner) (Date)				
	The terminalmonths of this patent have been disclaimed.	(Legal Instrumenta Examiner) (Date)			ISSUE BATCH NUMBER	
	e a constant	(2000	to Late(Mail)			